


CTE01-62 Series



Part No.	Current ratio (A)	Acc.Class (%)	Burden (VA)	mm/inch		
				OD (max)	ID (max)	H (max)
CTE01-62-500-31L	50/5	±3%	2	$\frac{62.70}{2.47}$	$\frac{26.81}{1.06}$	$\frac{25.40}{1.00}$
CTE01-62-600-31L	60/5	±2%	2			
CTE01-62-750-31L	75/5	±2%	2			
CTE01-62-800-31L	80/5	±2%	2			
CTE01-62-101-31L	100/5	±1%	2			
CTE01-62-121-31L	120/5	±1%	2.5			
CTE01-62-121-32L	125/5	±1%	2.5			
CTE01-62-151-31L	150/5	±1%	4			
CTE01-62-201-31L	200/5	±1%	4			
CTE01-62-251-31L	250/5	±1%	6			
CTE01-62-301-31L	300/5	±1%	8			

Remark:

1. Frequency band :50Hz~60Hz.
2. Operating temperature: -25°C~80°C.
3. All current ,voltage refer to rms value.
4. RoHS compliant.
5. Hi-Pot: 2500V_{RMS}/1min between windings.
6. Product parts meet UL requirements.

Definition:

- Current ratio :** Primary / Secondary Current.
- Burden :** Loaded Resistances.