



CTE02-104 Series



Electrical Characteristic				Mechanical Dimensions		
Part No.	Current ratio (A)	Acc.Class (%)	Burden (VA)	mm/inch		
				OD (max)	ID (max)	H (max)
CTE02-104-101-31S	100/5	±1%	1.0	104.35 4.11	52.60 2.07	107.35 4.23
CTE02-104-151-31S	150/5	±1%	5.0			
CTE02-104-201-31S	200/5	±1%	5.0			
CTE02-104-251-31S	250/5	±1%	7.5			
CTE02-104-301-31S	300/5	±1%	12.5			
CTE02-104-401-31S	400/5	±1%	15.0			
CTE02-104-501-31S	500/5	±1%	25.0			
CTE02-104-601-31S	600/5	±1%	30.0			
CTE02-104-751-31S	750/5	±1%	30.0			
CTE02-104-801-31S	800/5	±1%	35.0			
CTE02-104-102-31S	1000/5	±1%	35.0			
CTE02-104-122-31S	1200/5	±1%	40.0			
CTE02-104-152-31S	1500/5	±1%	50.0			

Remark:

1. Frequency band :50Hz~60Hz.
2. Operating temperature: -25℃~80℃.
3. All current ,voltage refer to rms value.
4. RoHS compliant.
5. Hi-Pot: 2500V_{RMS}/1min between windings.
6. Product parts meet UL requirements.

Definition:

Current ratio : Primary / Secondary Current.
Burden : Loaded Resistances.