



CTE02-89 Series



Electrical Characteristic				Mechanical Dimensions		
Part No.	Current ratio (A)	Acc.Class (%)	Burden (VA)	mm/inch		
				OD (max)	ID (max)	H (max)
CTE02-89-500-31S	50/5	±1%	1.0	89.95 3.54	39.85 1.57	96.15 3.79
CTE02-89-500-36S	50/5	±2%	1			
CTE02-89-750-31S	75/5	±1%	1.0			
CTE02-89-750-36S	75/5	±2%	1.5			
CTE02-89-101-31S	100/5	±1%	1.0			
CTE02-89-101-36S	100/5	±2%	2			
CTE02-89-151-31S	150/5	±1%	5.0			
CTE02-89-151-36S	150/5	±1%	5			
CTE02-89-201-31S	200/5	±1%	5.0			
CTE02-89-201-36S	200/5	±1%	5			
CTE02-89-251-31S	250/5	±1%	12.5			
CTE02-89-251-36S	250/5	±1%	10			
CTE02-89-301-31S	300/5	±1%	15.0			
CTE02-89-301-36S	300/5	±1%	12.5			
CTE02-89-401-31S	400/5	±1%	20.0			
CTE02-89-401-36S	400/5	±1%	12.5			
CTE02-89-501-31S	500/5	±1%	25.0			
CTE02-89-501-36S	500/5	±1%	20			
CTE02-89-601-31S	600/5	±1%	30.0			
CTE02-89-601-36S	600/5	±1%	25			
CTE02-89-751-31S	750/5	±1%	30.0			
CTE02-89-751-36S	750/5	±1%	25			
CTE02-89-801-31S	800/5	±1%	30.0			
CTE02-89-801-36S	800/5	±1%	25			
CTE02-89-102-31S	1000/5	±1%	35.0			
CTE02-89-102-36S	1000/5	±1%	25			
CTE02-89-122-31S	1200/5	±1%	40.0			
CTE02-89-122-36S	1200/5	±1%	30			

Remark:

1. Frequency band :50Hz-60Hz.
2. Operating temperature: -25°C~80°C.
3. All current ,voltage refer to rms value.
4. RoHS compliant.
5. Hi-Pot: 2500V_{RMS}/1min between windings.
6. Product parts meet UL requirements.

Definition:

Current ratio : Primary / Secondary Current.
Burden : Loaded Resistances.