


CTE04-74 Series



Electrical Characteristic								Mechanical Dimensions		
Part No.	IR (A)	Is (A)	RL (Ω)	KV	Primary Turns	Acc.Class (%)	Rates (VA)	mm/inch		
								L(max)	H(max)	H(max)
CTE04-74-201-31S	200	0.5	4	0.66	1	0.5,1.0	5	$\frac{74.9}{2.95}$	$\frac{41.55}{1.64}$	$\frac{99.85}{3.93}$
CTE04-74-251-31S	250	0.5	4	0.66	1	0.5,1.0	5			
CTE04-74-301-31S	300	0.5	4	0.66	1	0.5,1.0	5			
CTE04-74-401-31S	400	0.5	4	0.66	1	0.5,1.0	5			
CTE04-74-501-31S	500	0.5	4	0.66	1	0.5,1.0	5			
CTE04-74-601-31S	600	0.5	4	0.66	1	0.5,1.0	5			

Remark:

1. Frequency band :50Hz~60Hz.
2. Operating temperature: -25°C~80°C.
3. All current ,voltage refer to rms value.
4. RoHS compliant.
5. Hi-Pot: 2500V_{RMS}/1min between windings.
6. Product parts meet UL requirements.

Definition:

- Current ratio :** Primary / Secondary Current.
- Burden :** Loaded Resistances.